

護理機器人



Medicare Robot

指導老師：連震杰 教授

專題生：林晉暘、黃郁翔、黃堯、張少鈞

June 8, 2022

Outline

- 1.0 Motivation, Objective, and Scenario
- 2.0 System Setup, Function, and Flowchart
- 3.1 Two-Staged Navigation
- 3.2 Human Following Using Yolo v2
- 3.3 Visual-Guided Robot Arm Control
- 3.4 Learning-Based Face Recognition
- 3.5 Graphical User Interface (GUI)
- 4.0 Experimental Result

1.0 Motivation and Objective

■ Motivation:

在COVID-19的疫情肆虐下，護理師...

1. 作業壓力增加
2. 接觸感染風險增加



■ Objective:

打造一台防疫機器人，能夠...

1. 輔助照顧病人
2. 減少非必要接觸
3. 勝任日常工作
4. 緊急情況提供協助

1.0 Scenario

- 
1. 根據醫療人員指示**拿取**相對應的**藥物**
 2. 跟著醫療人員或**導航**移動至病床
 3. **確認**病人身分
 4. 聽從醫療人員指示**給予藥物**
 5. **自行走回**藥庫待命

1.0 Scenario

1. 根據醫療人員指令拿取相對應物品放到平台

在護理站



拿消毒水



偵測酒精噴灑器、藥盒位置

ArUco



把物體從桌面放入平台



2. 跟著醫療人員或自行導航移動至病床

日常巡航




Lidar




讀取地圖

Using ICP
Point Cloud
Matching



導航移動、避障



緊急情況



RGB-D Cam



偵測人的位置

Using yolov2



跟著人移動



1.0 Scenario



3. 尋找病患



確認病患資訊



偵測臉部




取得病患資訊



4. 聽從醫療人員指示給予藥物




給他退燒藥
酒精消毒



偵測酒精噴灑器、
藥盒位置

ArUco



夾取並把物體
放在病床



5. 自行走回倉庫




回去待命



讀取地圖




導航移動、避障



1.0 Contribution

- 林晉暘
 - 1) Navigation with 3D Lidar
 - 2) Learning-Base Face Recognition
 - 3) Robot Arm Integration
- 張少鈞
 - 1) GUI
 - 2) System Integration
 - 3) Aruco
- 黃郁翔、黃堯
 - 1) Human Following by Yolo v2
 - 2) Gripper Control
 - 3) Arm Control

2.0 System Setup



1. Eih RGB-D 深度相機

Realsense D415
辨識物品

2. 機械手臂、夾爪

抓取、給予物品以及
移動相機

ROS
Ubuntu 20.04
Wi-Fi


3. 3D Lidar

VLP-16
建置三維點雲地圖
進行定位導航

4. 自走車

移動至目標地點


2.0 System Functions




Sensor	攝影機	3D Lidar 光達
探測角度	30°	360°
測距精度	低	高
頻率	低	高
成本	適中(6000元)	高(90000元)
環境限制	影像模糊與光度影響	大雨或透明玻璃

2.0 System Flowchart

Graphical User Interface




3.1 Two-Stage Navigation




3.2 Human Following Using Yolo v2

速度



Extract Depth of Box Center




RGB-D camera

Human Following

1. **Video Stream**: Subscribe to realsense RGB and Depth image, run yolov2 in darknet and ROS environment.
2. **Detect Human**: Draw bounding box only when human is detected and extract box center.
3. **Distance estimation**: extract the depth data by bounding box and RGB-D camera.
4. **Output velocity command**: Move faster if distance is far, slower if close.
5. **Handle exception**: Stop immediately if no person is detected or the person is too far away.


3.3 Visual-Guided Robot Arm Control



1. Identify all objects with ArUco
2. Get ArUco id to find the target object
3. Calculate the translation and then pick up the object

ArUco

- 1) **Video Stream:** Subscribe realsense RGB image msgs.
- 2) **Pose Estimation:** Get ArUco object to camera transform.
- 3) **Coordinate transform:** camera frame to gripper frame.
- 4) **Robot Arm Control:** Grab/Put the object to target place.



3.4 Learning-Based Face Recognition

Database Image



Real-time image



John

Sam


Yao Hwang

Unknown

Face Recognition (D-lib)



1. **Create database:** save the image and save face encoding of each person to the folder.
2. **Video Stream:** Subscribe realsense RGB image msgs.
3. **Recognize:** Using real sense camera and start recognizing.
4. **Comparison:** Compare the image display on real-sense with the image in database.
5. **Result:** Draw the box and print out the persons name, or "Unknown".

3.5 Graphical User Interface (GUI)




3.5 Graphical User Interface (GUI)

- 1.1) Node Checker
 - Check ROS node is available or not
- 1.2) Amm Control
 - Control AMM by clicking the button
 - Set speed
- 1.3) Arm Control
 - Monitor Robot Arm position
 - Set increment
 - Interrupt Robot Arm



- 2) Gripper control
 - Active
 - Reset
 - Open
 - Close



- 3) Set TM to pre-defined position
 - Init_Pos
 - Grab item
 - Yolo_Pos
 - Follow human

4.0 Experimental Results